


3073F Twinax - DataTray® 600V Twinaxial Cable



For more Information
please call

1-800-Belden1



Description

18 AWG stranded (7x26) tinned copper conductors, flame-retardant polyolefin insulation, overall Beldfoil® (100% coverage) plus a tinned copper braid shield (55% coverage), sunlight resistant PVC jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1.000	18	7x26	TC - Tinned Copper	0.046

Insulation:

Insulation Material

Ins Material	Dia. (in.)
FRPO - Flame Retardant Polyolefin	0.123

Outer Shield:

Outer Shield Material

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	55

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

Outer Shield Drain Wire Diameter .038

Outer Jacket:

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling:

Overall Nominal Diameter: .388 in.

Pair:

Pair Color Code Chart

Number	Color
1	Natural
2	Blue

Mechanical Characteristics (Overall):

Operating Temperature Range -40°C To +75°C

UL Temperature Rating 75°C Dry

Bulk Cable Weight: 61 lbs/1000 ft.

Max. Recommended Pulling Tension: 90 lbs.

Min. Bend Radius (Install): 4 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification CMG, PLTC, ITC, TC

3073F Twinax - DataTray® 600V Twinaxial Cable

CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	10/13/2005

Flame Test:

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT1, FT4

Suitability:

Sunlight Resistance	Yes
---------------------	-----

Plenum/Non-Plenum:

Plenum (Y/N)	N
--------------	---

Electrical Characteristics (Overall):

Nominal Input Impedance

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Impedance (Ohm)
	1.000			100.000

Nom. Inductance

Inductance (µH/ft)
0.150

Nom. Mutual Capacitance

Capacitance (pF/ft)
15.300

Nominal Velocity of Propagation

VP (%)
64.500

Nominal Delay

Delay (ns/ft)
1.580

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
6.900

Nom. Attenuation

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 ft.)
	1.000			0.410
	10.000			1.330
	50.000			2.970
	100.000			4.200
	200.000			5.950
	400.000			7.520

Max. Operating Voltage - UL

Voltage
600 V RMS (NEC Type TC)

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
2.900

Notes (Overall):

Notes CPE Jacket Optional.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Jacket Color	Notes	Item Desc
--------	-------	-------------	--------------	-------	-----------

3073F Twinax - DataTray® 600V Twinaxial Cable

3073F C551000	1,000 FT	85.000 LB	BLUE, CAIRO	C	#18 FS PR FRPP SH PVC BLUCAI
3073F C555000	5,000 FT	420.000 LB	BLUE, CAIRO	C N	#18 FS PR FRPP SH PVC BLUCAI

Notes:

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 05-14-2007

© 2007 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS), EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.