


82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable



For more Information
 please call
 1-800-Belden1



Description

Low cap 24 AWG stranded (7x32) TC conductors, plenum, foam FEP insulation, twisted pairs, overall Beldfoil (100% coverage) + TC braid shield (90% coverage), 24 AWG stranded TC drain wire, Flamarrest® jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Pairs	AWG	Stranding	Conductor Material
2,000	24	7x32	TC - Tinned Copper

Insulation:

Insulation Material

Ins Trade Name	Ins Material
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene

Outer Shield:

Outer Shield Material

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

Outer Shield Drain Wire AWG

AWG	Stranding	Drain Wire Conductor Material
22	7x32	TC - Tinned Copper

Outer Jacket:

Outer Jacket Material

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Overall Cabling:

Overall Nominal Diameter: .273 in.

Pair:

Pair Color Code Chart

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White

Pair Lay Length & Direction

Lay Length (in.)	Twists/ft. (twist/ft)
2.000	6.000

Mechanical Characteristics (Overall):

Operating Temperature Range	0°C To +75°C
Bulk Cable Weight:	38 lbs/1000 ft.
Max. Recommended Pulling Tension:	56.700 lbs.
Min. Bend Radius (Install):	2.750 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	10/01/2005
Flame Test:	
UL Flame Test	NFPA 262
C(UL) Flame Test	FT6
Plenum/Non-Plenum:	
Plenum (Y/N)	Y
Non-Plenum Number	9842

Electrical Characteristics (Overall):

Nom. Characteristic Impedance

Impedance (Ohm)
120.000

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)
12.000

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/ft)
22.000

Nominal Velocity of Propagation

VP (%)
76

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
24.000

Max. Operating Voltage - UL

Voltage
300 V RMS

Max. Recommended Current

Current
3.2 Amps per conductor @ 25°C

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
2.400

Notes (Overall):

Notes Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Jacket Color	Notes	Item Desc
82842 8771000	1,000 FT	42.000 LB	NATURAL	C	2 PR #24 FFEP SH FLRST NAT
82842 877500	500 FT	19.000 LB	NATURAL	C	2 PR #24 FFEP SH FLRST NAT

Notes:

C = CRATE REEL PUT-UP.

82842 Multi-Conductor - Low Capacitance Computer and Computer P.O.S. Cable

© 2007 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.